

ERL MAINTENANCE SUPPORT SDN BHD

Co. Reg. No. 199901023674 (498574-T)











SYSTEMS (SYS) DEPARTMENT

SIGNALLING (SIG) MAINTENANCE TECHNICAL INSTRUCTION

Ref. No. E00.OME.M12950.BT. 1001.A

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 2 of 94	Signalling (SIG) Maintenance Technical Instruction

Release

Released:	f	Ham Mow Wai	Maintenance	19.1.22	
Checked:	f	Anthony Arokianathan	Systems	19.1.22	
Checked:		Noel Devan	Systems	19 Jan 22	
Checked:		Tengku Nadzuan	Systems	01.12.2021	
Checked:		Laxchumy	Systems	07/10/2021	
Checked:		Mohd Hasan	Systems	13/10/21	
Checked:		Azuansyamsany	Systems	17.01.2022	
Author:		Asmawi Jusoh	Systems	7/10/21	
		Name	Dept.	Date	Signature

Amendments or additions to this procedure must be indicated with a vertical black line in the adjacent left margin.

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 3 of 94	Signalling (SIG) Maintenance Technical Instruction

Change Record and Configuration Control

A	26.8.2021	Department re-structuring (ELT and SIG Merged into SYSTEMS) and Technical Instruction updated.	Tengku Nadzuan and Asmawi
Revision	Date	Modification	Name

Planning Of Changes Reference For Revision: E00.OME.M12950.BT.1001.A					
Issues To Consider	Checked (<i>Please mark X</i>)				Remarks
1) Are there any negative impact?	YES		NO	X	
2) Will the integrity of QEMS be affected?	YES		NO	X	
3) Resources available?	YES	X	NO		
4) Allocation or relocation of responsibilities and authorities required?	YES		NO	X	

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 4 of 94	Signalling (SIG) Maintenance Technical Instruction

TABLE OF CONTENTS

	Page
1 Purpose	6
2 Scope, Distribution & Access.....	6
3 Axle Counter Maintenance Technical Instruction.....	7
3.1 Resetting an Axle Counter	7
3.2 Re-tuning ASB Card	8
3.3 Replacement of ZBG Card.....	10
3.4 Replacement of ASB Card.....	11
3.5 Replacement of Wheel Sensor	12
3.6 Axle Counter Failure Rectification Works.....	13
4 Point Machine Maintenance Technical Instruction (Siemens and AZD Praha).....	15
4.1 Point Machine Detection Missing.....	15
4.2 Point Machine “Detection Missing” and “Trailed”	16
4.3 Replacement of SIWES	17
4.4 Point Machine (No Go) Test	18
4.5 Point Machine (GO) Test	19
4.6 Replacement of Point Control Unit (PCU).....	20
4.7 Point Control Unit (PCU) Relay Condition.....	21
5 ATP Maintenance Technical Instruction.....	22
5.1 ATP Trainbone.....	22
5.1.1 Confirming the Track Data for Train.....	22
5.1.2 Changing of Train Data in Units.....	23
5.1.3 Changing of train Data in Absolute Numbers.....	24
5.1.4 Keying new Time and Date at MMI.....	25
5.1.5 Keying New Wheel Diameter	26
5.1.6 Checking for Fault On the MMI	27
5.1.7 Clearing ATP Fault and Releasing the EB via MMI	27
5.1.8 Keying in New Position and Track number.	28
5.1.9 No Telegram Fault message.....	29
5.1.10 Lost Position fault.....	30
5.1.10 Lost Position fault (Continued).....	31
5.1.11 Train ATP Computer Download	32
5.1.12 Real Time Monitoring on ATP diagnostic software	32
5.1.13 Position Measuring Probe Failure.....	33
5.1.14 Replacement of Wheel Pulse Generator.....	34
5.1.15 Wheel Pulse Generator Commissioning	35
5.2 ATP Indoor.....	37
5.2.1 Downloading ATP Computer in Interlocking	37
5.2.2 Inserting Speed Restriction from Interlocking	38
5.2.3 Inserting Speed Restriction from OCC.....	39
5.2.4 Check Inserting Speed Restriction from Interlocking.	40
5.2.5 Cancelling Speed Restriction (Interlocking and OCC)	40
5.2.6 Clearing of ATP fault (via OCC MMI & Interlocking MMI)	41
5.2.7 ATP Station borders and overlaps	41
5.3 ATP Outdoor.....	44
5.3.1 Measurement of Impedance Transformer.....	44
5.3.2 Measurement of SLA	45

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 5 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3.3	Reading the ATP Telegram Using Train	46
5.3.4	Measurement of ATP loop cable resistance	47
5.3.5	IW, Transmitter and ATP loop configuration	48
6	Signal Maintenance Technical Instruction.....	55
6.1	Signal Transformer Voltage & Current Measurement	55
6.2	Signal Transformer Voltage Measurement - Shunt Signal	56
6.3	Call ON Signal Voltage Measurement	57
6.4	Colour Light Signals Failure.....	58
6.5	LED Shunt & Shunt Signal Failure.....	59
6.6	LED Signal Failure (KA S21, KA S24, KA RS21 and KA RS24).....	60
6.7	LED Signal Failure (KA T31 and KA T34).....	61
6.8	Signal Route Indicator Failure.....	62
6.9	LED Route Indicator Failure (KA T31, KA T34, KA S21 and KA S24)	63
7	Cable Maintenance Technical Instruction	64
7.1	Cable Megger Testing.....	64
7.2	Correspondence Test – Main Signal for Color Light Signal	65
7.2	Correspondence Test- Main Signal for Color Light Signal (continued)	66
7.3	Correspondence Test – LED Signal.....	67
7.3	Correspondence Test – LED Signal (continued).....	68
7.4	Correspondence Test – Shunt Signal	69
7.4	Shunt Signal Correspondence Test (continued)	70
7.5	LED Shunt Signal Correspondence Test – LED Shunt Signal	71
7.5	LED Shunt Signal Correspondence Test (continued)	72
7.6	Correspondence Test – Call On Signal.....	73
7.6	Correspondence Test- Call On signal (continued)	74
7.7	Correspondence Test – Point Machine.....	75
7.7	Correspondence Test- Point Machine (continued).....	76
7.8	Correspondence Test – Wheel Sensor.....	77
8	PIDS Maintenance Technical Instruction For SAF Model and Industronic Model.....	78
8.1	To Replace LCC531 Power Control / RS-485 Communication Board (SAF).....	78
8.2	To Replace LCC500 Micro- Controller Board.....	79
8.3	To Change LCD Module (SAF).....	80
8.4	To Change Converter Card (SAF)	81
8.5	Process for Soft Reset FIA PIDS Software (SAF).....	82
8.6	To Change Power Supply Unit (PSU) for PIDS Display (Industronic Model).....	83
8.7	To Change Controller Card for PIDS Display (Industronic Model).....	84
8.8	LED Module Display Card Replacement (Industronic Model).....	85
9	TMS Maintenance Technical Instruction.....	86
9.1	Functions of Abbreviation in the Timetable Planning	86
9.2	Checking and Testing Data Transfer Tools on CST 70 and CST 71.	87
9.3	TSP task fail to export to File exchange server.....	88
9.4	Key in the TMS username and download the log File.....	90
9.5	Perform Task TSP using CD/DVD Rom at ILTIS workstation	91
9.6	Restoration of YST 28 or YST 29 or both goes down.	92
10	OPERATING INSTRUCTION FOR UPS (Uninterruptable Power Supply).....	93
10.1	UPS Maintenance START-UP Procedure	93
10.2	UPS Maintenance BY-PASS Procedure.....	94

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 6 of 94	Signalling (SIG) Maintenance Technical Instruction

1 Purpose

- 1.1 This document provides a structured guidance / process flow for the purpose of maintenance on the various SYSTEMS - Signalling sub-systems.
- 1.2 This Technical Instruction / process flow is extracted from the O&M Manual and also based on the experience acquired from the daily maintenance of the SYS- Sig sub-system.
- 1.3 The guidance / process flow outlined in this document shall be used by all SYS-Sig personnel for carrying out maintenance activities as and when required.

2 Scope, Distribution & Access


- 2.1 This document is specific for the various SYS - Sig sub-systems used in the ERL system.
- 2.2 A hardcopy of this document shall be made available for each SYS - Sig personnel as a personal guide. This document can also be accessed electronically via the common shared folder and Electronic Documentation Maintenance System (EDMS).

If there is any doubt in the references provided below, please refer to your superior immediately.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 7 of 94	Signalling (SIG) Maintenance Technical Instruction


3 Axle Counter Maintenance Technical Instruction

3.1 Resetting an Axle Counter




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 8 of 94	Signalling (SIG) Maintenance Technical Instruction

3.2 Re-tuning ASB Card




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 9 of 94	Signalling (SIG) Maintenance Technical Instruction

3.2 Re-tuning ASB Card (Continued)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 10 of 94	Signalling (SIG) Maintenance Technical Instruction

3.3 Replacement of ZBG Card




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 11 of 94	Signalling (SIG) Maintenance Technical Instruction

3.4 Replacement of ASB Card




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 12 of 94	Signalling (SIG) Maintenance Technical Instruction

3.4 Replacement of ASB Card (Continued)




3.5 Replacement of Wheel Sensor




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 13 of 94	Signalling (SIG) Maintenance Technical Instruction

3.6 Axle Counter Failure Rectification Works



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 14 of 94	Signalling (SIG) Maintenance Technical Instruction


3.6 Axle Counter Failure Rectification Works (Continued)



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 15 of 94	Signalling (SIG) Maintenance Technical Instruction

4 Point Machine Maintenance Technical Instruction (Siemens and AZD Praha)


4.1 Point Machine Detection Missing



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 16 of 94	Signalling (SIG) Maintenance Technical Instruction


4.2 Point Machine “Detection Missing” and “Trailed”

Do not adopt any shortcut method during this process



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 17 of 94	Signalling (SIG) Maintenance Technical Instruction


4.3 Replacement of SIWES



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 18 of 94	Signalling (SIG) Maintenance Technical Instruction


4.4 Point Machine (No Go) Test

Do not adopt any shortcut method during this process




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 19 of 94	Signalling (SIG) Maintenance Technical Instruction

4.5 Point Machine (GO) Test



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 20 of 94	Signalling (SIG) Maintenance Technical Instruction

4.6 Replacement of Point Control Unit (PCU)



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 21 of 94	Signalling (SIG) Maintenance Technical Instruction

4.7 Point Control Unit (PCU) Relay Condition

PCU relay condition for point set to Left

LL ↑	PR ↓	ST ↓	AN ↓	AM ↓	TIMER
LR ↓	L ↓	ST ↑	AN ↓	UL ↑	UR ↓

PCU relay condition for point set to Right

LL ↓	PR ↓	ST ↓	AN ↓	AM ↓	TIMER
LR ↑	L ↑	ST ↑	AN ↓	UL ↓	UR ↑

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 22 of 94	Signalling (SIG) Maintenance Technical Instruction

5 ATP Maintenance Technical Instruction

5.1 ATP Trainbone


5.1.1 Confirming the Track Data for Train

Note: the train data has to be confirmed before the train can be moved.

The description of the train data is as given below:

- L1U : Length of one train = 68m or 1u
- B2C : Brake code 2 = 65% or 2C
- V160 : Maximum running speed = 160km/h Currently speed 145km/h until further notice.


Follow the process below to confirm train data:



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 23 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.2 Changing of Train Data in Units


NOTE: Train Units
L= 1u
B= 2u
V= 145km/h



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 24 of 94	Signalling (SIG) Maintenance Technical Instruction


5.1.3 Changing of train Data in Absolute Numbers

NOTE: Train Units
L= 1u
B= 2u
V= 145km/h




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 25 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.4 Keying new Time and Date at MMI




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 26 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.5 Keying New Wheel Diameter




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 27 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.6 Checking for Fault On the MMI



5.1.7 Clearing ATP Fault and Releasing the EB via MMI


NOTE: Reset and clearing of ATP fault can be done only when the train is at complete stop.



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 28 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.8 Keying in New Position and Track number.


Note: For Depot, use position = 40, Track 0



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 29 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.9 No Telegram Fault message

Note:
1. First train already in the section when telegram is lost will have an EB with the message. "Signal_stop"
2. Next trains coming to the loop will record the message "No Telegram"




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 30 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.10 Lost Position fault

Note: Loss of position can be occurred due to the following three reasons:

- i) Incorrect wheel diameter
- ii) Calibrating magnet (Track site) not detected i.e.: magnet missing or faulty magnetic receiver
- iii) Internal error of the ATP Trainborne computer

Train had an EB with the message “ZSI Sector 0” and “position”. Request train drivers to reset and follow the procedure as in 5.1.8 (page 28)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 31 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.10 Lost Position fault (Continued)


Trainborne MMI Blank / Hang after EB.

- Request OTD to **hard reset the MCB for ATP** in Cab A1 or Cab B1 for 10Second.
- Hard Reset done. **Mandatory for OTD to key in the new correct position and track number.**
 - OTD need to re-enter **Position [40km] and Track number [0], Drive below 25Km/h** until reached and aligned to the KM-Board, between OCL pole and train driver window.
 - With KM-Board number, OTD need to inform and **retrieve new position and track number from OCC.**
 - **Enter new Position and Track number** given by OCC only.




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 32 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.11 Train ATP Computer Download



Note:
Ensure train is at stationary position when doing the ATP download.

5.1.12 Real Time Monitoring on ATP diagnostic software




Description on dropdown menu	Details
Display Speeds	Display actual speed of train (V-act) and maximum allowable speed by ATP (V-Moni)
Compare actual speeds	Compares the speed on all the calculators simultaneously. V-act (l, p, n) 0000,0000,0000
Compare positions	Compares the position of all the calculators simultaneously. Pos. (l, p, n) 0000000, 0000000,0000000
Real Odometer device	Shows the actual speed and the direction of travel. Vact: - 0000; dist + 0000000000
Receipt Cor. Telegram	Measures the telegram received at both the antenna. Channel 1/ Channel 2 0005/ 0006

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 33 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.13 Position Measuring Probe Failure

- Note:**
- 1) Wheel Pulse generator (WPG) is installed at axle no 5 (side 2) and 6 (side1).
 - 2) They are connected to the junction box by cables, which are labeled.
 - 3) After changing the wheel pulse generator, the new wheel pulse generator has to be commissioned.




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 34 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.14 Replacement of Wheel Pulse Generator

Note: Once the Wheel Pulse Generator is suspected/ identified to be faulty, the following process is to be followed.

Disconnect the wires in the junction box and Dismount the Wheel Pulse Generator from the wheel.

Re-connect the new Wheel Pulse Generator as in the diagram below



After the wheel pulse generator is connected, take the train to the test track and perform the commissioning test.

Refer 5.1.15 (page 34)

Once the commissioning test is completed, the train can be released for service.

DONE

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 35 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.15 Wheel Pulse Generator Commissioning

Note: Follow the following procedure and tick the provided YES or NO column. For any NO ticked, consult with SYS-ESD

Name	Staff ID	Signature	Train ID	Date

Wheel Pulse Generator 1 (Axle 05)

Switch Off trainborne ATP Computer.
 Disconnect DB connector for WPG02.
 Connect DB connector for WPG01.
 Switch ON trainborne ATP Computer.
 Connect the ATP diagnostic laptop to the ATP computer and select to view the real time for position.

- | | YES | NO |
|---|--------------------------|--------------------------|
| 1. Fault Indication no longer present. | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. Move train in direction of KLIA specific distance (min. 15m)
Position measurement indication positive (+ve) | <input type="checkbox"/> | <input type="checkbox"/> |
| 3. Speed Indication positive (+ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 4. After _____m LEDs 3 and 4 on the position measuring interface illuminate. | <input type="checkbox"/> | <input type="checkbox"/> |
| 5. The fault lamps on the Man Machine Interface on the display unit come ON. | <input type="checkbox"/> | <input type="checkbox"/> |
| 6. When the fault is queried, the message "Wheel Sensor 1" at MMI displayed. | <input type="checkbox"/> | <input type="checkbox"/> |

Move the Train the same distance forward (Direction KLS) using CAB 2

- | | | |
|--|--------------------------|--------------------------|
| 7. Position measurement indication negative (-ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 8. Speed indication negative (-ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 9. Move forwards at a defined speed in accordance with the analogue tachometer.
The indicated speed on the display unit is correct. | <input type="checkbox"/> | <input type="checkbox"/> |

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 36 of 94	Signalling (SIG) Maintenance Technical Instruction

5.1.15 Wheel Pulse Generator Commissioning (Continued)

Note: Follow the following procedure and tick the provided YES or NO column. For any NO ticked, consult with SYS-ESD.

Name	Staff ID	Signature	Train ID	Date

Wheel Pulse Generator 2 (Axle 06)

Switch Off trainborne ATP Computer.
 Disconnect DB connector for WPG01.
 Connect DB connector for WPG02.
 Switch ON trainborne ATP Computer.
 Connect the ATP diagnostic laptop to the ATP computer and select to view the real time for position.

- | | YES | NO |
|---|--------------------------|--------------------------|
| 1. Fault Indication no longer present. | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. Move train in direction of KLIA specific distance (min. 15m)
Position measurement indication positive (+ve) | <input type="checkbox"/> | <input type="checkbox"/> |
| 3. Speed Indication positive (+ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 4. After _____m LEDs 1 and 2 on the position measuring interface illuminate. | <input type="checkbox"/> | <input type="checkbox"/> |
| 5. The fault lamps on the Man Machine Interface on the display unit come ON. | <input type="checkbox"/> | <input type="checkbox"/> |
| 6. When the fault is queried, the message "Wheel Sensor 2" at MMI displayed. | <input type="checkbox"/> | <input type="checkbox"/> |

Move the Train the same distance forward (direction KLS) using CAB 2


- | | | |
|--|--------------------------|--------------------------|
| 7. Position measurement indication negative (-ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 8. Speed indication negative (-ve). | <input type="checkbox"/> | <input type="checkbox"/> |
| 9. Move forwards at a defined speed in accordance with the analogue tachometer.
The indicated speed on the display unit is correct. | <input type="checkbox"/> | <input type="checkbox"/> |

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 37 of 94	Signalling (SIG) Maintenance Technical Instruction

5.2 ATP Indoor

5.2.1 Downloading ATP Computer in Interlocking


Note: Ensure there are no trains moving in the section when doing the ATP download.



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 38 of 94	Signalling (SIG) Maintenance Technical Instruction


5.2.2 Inserting Speed Restriction from Interlocking

Note: Under normal condition, the ATP MMI in the interlocking is inactive and has to be activated by requesting from OCC.




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 39 of 94	Signalling (SIG) Maintenance Technical Instruction

5.2.3 Inserting Speed Restriction from OCC




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 40 of 94	Signalling (SIG) Maintenance Technical Instruction

5.2.4 Check Inserting Speed Restriction from Interlocking.




5.2.5 Cancelling Speed Restriction (Interlocking and OCC)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 41 of 94	Signalling (SIG) Maintenance Technical Instruction

5.2.6 Clearing of ATP fault (via OCC MMI & Interlocking MMI)




5.2.7 ATP Station borders and overlaps

KUALA LUMPUR SENTRAL (KLS)




BANDAR TASIK SELATAN (BTS)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 42 of 94	Signalling (SIG) Maintenance Technical Instruction


CROSSOVER (XA)



PUTRAJAYA (PCS)



SALAK TINGGI (STS)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 43 of 94	Signalling (SIG) Maintenance Technical Instruction

KUALA LUMPUR INTERNATIONAL AIRPORT (KA)

48'360


56'180



KUALA LUMPUR INTERNATIONAL AIRPORT 2 (KA2)

56'180

58'270.5




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 44 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3 ATP Outdoor


5.3.1 Measurement of Impedance Transformer

Note: You will require a scope meter or oscilloscope to do this measurement.




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 45 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3.2 Measurement of SLA




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 46 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3.3 Reading the ATP Telegram Using Train



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 47 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3.4 Measurement of ATP loop cable resistance



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 48 of 94	Signalling (SIG) Maintenance Technical Instruction

5.3.5 IW, Transmitter and ATP loop configuration

Station	Transmitter no:	IW & SLA	Signals and point affected	Call and Advise OCC
KLS	1	IW 01/01 (KM100+264) SLA 01/01 (KM100+000))	Signals: N34, T34, N33, T33, T32, N32, T31, N31, S27, N42 Points: 201,202,302,223,322,323,221	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 0-979 to KM 0-270. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	2	IW 01/ 02 (KM100+620) SLA 01/02 (KM1.400)	Signal: N23, N22, T42, T43, N13, N12, T3011, RN13, N2013 Points: 325,326,225,226	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 0-270 to KM1.400 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 01/03 (KM 3.400) SLA 01/03 (KM1.401)	Signal: T3021, N2023, T3023, N2029 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 1.400 to KM 3.700 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	4	IW 01/04 (KM 3.700) SLA 01/04 (KM5.876)	Signals: T3039, N2039, T3051, N2049 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 3.700 to KM 6.000. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 49 of 94	Signalling (SIG) Maintenance Technical Instruction

BTS	1	IW 08/01 (Km 8.29) SLA 08/01 (Km 5.88)	Signals: N2059, T3063, N2069, T3073, R T22 N2077, T23, T22 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 5.900 to KM 8.300. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	2	IW 08/02 (Km 8.93) SLA 08/02 (Km 8.23)	Signals; N31, N32, T31, T32, T33, T34, N33, N34 Points: 302,202,305.206,322,221,325,225	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 8.200 to KM 9.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 08/03 (Km 9.22) SLA 08/03 (Km 11.41)	Signals: N23, N22, T3097, RN 23, N2015, T3113 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 9.100 to KM 11.400. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
XA	1	IW 16/01 (KM 13.700) SLA 16/01 (KM 11.414)	Signals: N2115, T3125, N2125 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 11.400 to KM 13.700. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 50 of 94	Signalling (SIG) Maintenance Technical Instruction

XA	2	IW 16/02 (KM 13.700) SLA 16/02 (KM 15.800)	Signal: T3135, N2135, T3145, RT 22, N2151 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 13.7 to KM 15.8. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 16/03 (KM 17.100) SLA 16/03 (KM 15.801)	Signal: T23, T22, N33, N32 Points: 302,202	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 15.800 to KM 17.100. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	4	IW 16/04 (KM 17.101) SLA 16/04 (KM 19.200)	Signal: T33, N23, T32, N22, T3193 Points: 225, 325	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 17.1 to KM 19.200. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	5	IW 16/05 (KM 21.300) SLA 16/05 (KM 19.201)	Signal: RN 23, N 2195, T 3207, N 2207 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 19.200 to KM 21.300. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	6	IW 16/06 (KM 21.301) SLA 16/06 (KM 23.739)	Signal: N 2221. T 3227 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 21.300 to KM 23.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 51 of 94	Signalling (SIG) Maintenance Technical Instruction

PJS	1	IW 31/01 (KM26.050) SLA 31/01 (KM 23.740)	Signals: N2235, T 3247, N2251 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 23.500 to KM 26.100. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	2	IW 31/02 (KM26.050) SLA 31/02 (KM 28.500)	Signals: T 3267, N 2267, RT 12, N 2281 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 26.000 to KM 28.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 31/03 (KM 30.560) SLA 31/03 (KM 28.501)	Signal: T13, T12, N43, N42, T23, T22 Points: 302,202	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 28.500 to KM 30.600. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	4	IW 31/04 (KM 31.360) SLA 31/04 (KM 31.480)	Signals: N34, N33, N32, N31, T34, T33, T32, T31 Points: 305,206,322,221,325,225	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 30.600 to KM 31.700. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	5	IW 31/05 (KM 31.400) SLA 31/05 (KM 33.600)	Signals: N 23, N 22, T 3325 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 31.300 to KM 33.600. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 52 of 94	Signalling (SIG) Maintenance Technical Instruction

PJS	6	IW 31/06 (KM 36.000) SLA 31/06 (KM 33.601)	Signals: RN 23, T 3345, N 2341, N 2359 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 33.600 to KM 36.00. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	7	IW 31/07 (KM 36.001) SLA 31/07 (KM 38.418)	Signals: T 3361, T3377, N 2377 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 36.000 to KM 38.400 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
STS	1	IW 46/01 (KM 40.500) SLA 46/01 (KM 38.419)	Signals: T3397, N2397 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 38.400 to KM 40.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	2	IW 46/02 (KM 40.501) SLA 46/02 (KM 42.600)	Signals: T3415, RT 12, N 2417 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 40.500 to KM 42.600. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 46/03 (KM 44.155) SLA 46/03 (KM 42.601)	Signals: N53, T13, N52, T12, T15 Points: 302,202,206,106	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 42.600 to KM 44.100. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 53 of 94	Signalling (SIG) Maintenance Technical Instruction

STS	4	IW 46/04 (KM 45.999) SLA 46/04 (KM 44.055)	Signals: N43, T23, N42, T22 Points: 325	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 44.000 to KM 46.000 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	5	IW 46/05 (KM 45.920) SLA 46/05 (KM 44.570)	Signals: T35, N45, N46 Points: 106, 108, 508, 901	- Override all signal and points. - Speed restriction not required. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	6	IW 46/06 (KM 46.100) SLA 46/06 (KM 45.670)	Signals: N31, T32, T31, T36 Points: 114,115,216,221	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 45.800 to KM 46.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	7	IW 46/07 (KM 48.000) SLA 46/07 (KM 46.000)	Signals: N34, N33, T34, T33, N23, T 3476, N22 Points: 322, 325, 225	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 46.000 to KM 48.000. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
STS	8	IW 46/08 (KM 48.001) SLA 46/08 (KM 50.360)	Signals: RN 23, T 3491, N2487, T3503, N2503 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 48.000 to KM 50.400 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.


Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 54 of 94	Signalling (SIG) Maintenance Technical Instruction

KLIA	1	IW 55/01 (KM 52.500) SLA 55/01 (KM 50.361)	Signals: T3517, N2517, N2503 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 50.200 to KM 52.500. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	2	IW 55/02 (KM 52.501) SLA 55/02 (KM 54.700)	Signals: T3533, N2533, RT12, T13, T12, N2541 Points: Nil	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 52.500 to KM 54.7. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
	3	IW 55/03 (KM 54.701) SLA 55/03 (KM 56.140)	Signals: N43, N42, T23, N33, T33, N34, T34, S24, T44 Points: 302,203,303,322,421,425,426	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 54.700 to KM 56.1 Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.
KLIA2	4	IW 55/04 (KM 55.015) SLA 55/04 (KM 58.256)	Signals: N32, T32, T31, S21, T41, RS21, RS24 Points: 201203,303,221,122,125,126,425,426	- Override all signal and points. - All trains shall proceed with max speed lower than 80km/h from KM 55.000 to KM 58.256. Note: Advice OCC to run Trains via Bi-directional and override element if the Trains EB for 2 or more consecutive signal occurred.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 55 of 94	Signalling (SIG) Maintenance Technical Instruction


6 Signal Maintenance Technical Instruction

6.1 Signal Transformer Voltage & Current Measurement




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 56 of 94	Signalling (SIG) Maintenance Technical Instruction

6.2 Signal Transformer Voltage Measurement - Shunt Signal




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 57 of 94	Signalling (SIG) Maintenance Technical Instruction

6.3 Call ON Signal Voltage Measurement




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 58 of 94	Signalling (SIG) Maintenance Technical Instruction

6.4 Colour Light Signals Failure




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 59 of 94	Signalling (SIG) Maintenance Technical Instruction

6.5 LED Shunt & Shunt Signal Failure




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 60 of 94	Signalling (SIG) Maintenance Technical Instruction

6.6 LED Signal Failure (KA S21, KA S24, KA RS21 and KA RS24)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 61 of 94	Signalling (SIG) Maintenance Technical Instruction

6.7 LED Signal Failure (KA T31 and KA T34)




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 62 of 94	Signalling (SIG) Maintenance Technical Instruction

6.8 Signal Route Indicator Failure



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 63 of 94	Signalling (SIG) Maintenance Technical Instruction


6.9 LED Route Indicator Failure (KA T31, KA T34, KA S21 and KA S24)



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 64 of 94	Signalling (SIG) Maintenance Technical Instruction

7 Cable Maintenance Technical Instruction


7.1 Cable Megger Testing



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 65 of 94	Signalling (SIG) Maintenance Technical Instruction


7.2 Correspondence Test – Main Signal for Color Light Signal

This test to be conducted after repairing or replacing of cables and also after continuity and megger test. Route is in released condition. Main and shunt signal is at “stop” aspect, Call ON signal is blank.



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 66 of 94	Signalling (SIG) Maintenance Technical Instruction

7.2 Correspondence Test- Main Signal for Color Light Signal (continued)



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 67 of 94	Signalling (SIG) Maintenance Technical Instruction

7.3 Correspondence Test – LED Signal

This test to be conducted after repairing or replacing of cables and also after continuity and megger test. Route is in released condition. Main and shunt signal is at “stop” aspect, Call ON signal is blank.

Connect the equipment to interlocking by inserting the links at location and interlocking.

Check the aspect of the signal, must show RED.

Confirm with OCC the same aspect is showed on TMS.

Remove RED aspect LED wires

Check the status of RM relay. It must drop.

Check TMS message. “Main aspect and Shunt Aspect or Shunt Aspect only” must appear.

Restore / Replace the LED Module

TMS fault message must disappear.

Check in Interlocking the signal control relays HS/VS must be down for Main Signal


Request OCC to clear only the signal under test, ahead signal must be RED.

Check in interlocking the signal control relays HS must pick up for Main Signal.

Check the aspect of the signal


<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 68 of 94	Signalling (SIG) Maintenance Technical Instruction

7.3 Correspondence Test – LED Signal (continued)




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 69 of 94	Signalling (SIG) Maintenance Technical Instruction

7.4 Correspondence Test – Shunt Signal




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 70 of 94	Signalling (SIG) Maintenance Technical Instruction

7.4 Shunt Signal Correspondence Test (continued)




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 71 of 94	Signalling (SIG) Maintenance Technical Instruction

7.5 LED Shunt Signal Correspondence Test – LED Shunt Signal




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 72 of 94	Signalling (SIG) Maintenance Technical Instruction

7.5 LED Shunt Signal Correspondence Test (continued)




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 73 of 94	Signalling (SIG) Maintenance Technical Instruction

7.6 Correspondence Test – Call On Signal



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 74 of 94	Signalling (SIG) Maintenance Technical Instruction

7.6 Correspondence Test – Call On signal (continued)



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 75 of 94	Signalling (SIG) Maintenance Technical Instruction

7.7 Correspondence Test – Point Machine

This test to be conducted after repairing or replacing of cables or point machine and also after continuity and megger test. Route is in released condition. Point is unlocked. MCB for the said Point machine (3phase & 48vdc) is OFF. Set Point-lock (scotch) to the same position as the PCU last operated position.

Confirm with OCC that no movement of vehicles over the point during testing.

Check the point position is in correspondence with the PCU UL/ UR relay position.

In case the point is moved manually for traffic movements, it must be brought to the same position as the PCU last called position.

Connect the equipment to interlocking by inserting the links at point machine (site) and interlocking.

Switch ON MCB for the said Point machine (3phase and 48vdc)

Check the detection relays. Either UL/ UR relay must pick up depending on the point position and proceed. If not, follow the point detection missing procedure in item 4.1 (page 15)

Consider the UL relay is picked up and point is left position.


Check with OCC that the point under test must indicate left on TMS

Remove the point-lock (scotch).

Request OCC to move the point from left to right.


<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 76 of 94	Signalling (SIG) Maintenance Technical Instruction

7.7 Correspondence Test – Point Machine (continued)



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 77 of 94	Signalling (SIG) Maintenance Technical Instruction


7.8 Correspondence Test – Wheel Sensor



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 78 of 94	Signalling (SIG) Maintenance Technical Instruction


8 PIDS Maintenance Technical Instruction For SAF Model and Industronic Model.

8.1 To Replace LCC531 Power Control / RS-485 Communication Board (SAF)




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 79 of 94	Signalling (SIG) Maintenance Technical Instruction

8.2 To Replace LCC500 Micro – Controller Board




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 80 of 94	Signalling (SIG) Maintenance Technical Instruction

8.3 To Change LCD Module (SAF)




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 81 of 94	Signalling (SIG) Maintenance Technical Instruction

8.4 To Change Converter Card (SAF)



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 82 of 94	Signalling (SIG) Maintenance Technical Instruction


8.5 Process for Soft Reset FIA PIDS Software (SAF)



Note:
Soft-reset only can be done at Depot Interlocking and after approval from Supervisor or Superior and OCC.

<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 83 of 94	Signalling (SIG) Maintenance Technical Instruction

8.6 To Change Power Supply Unit (PSU) for PIDS Display (Industronic Model).



Note:
Tools Required:

- Philip Screwdriver
- M3 Screw nut Driver
- M43 Screw nut Driver

PIDS Display Type:


- Type A: Only at KLIA2
- Type B: Only at KLIA
- Type C: KLIA & KLIA2
- Type D: Only at KLIA2

For PIDS Displays (Type A, B, C)

No.	Component	Part Name & Model
1	Power Supply Unit (PSU) for Type A	Meanwell, S-320-5
2	Power Supply Unit (PSU) for Type B & C	Meanwell, NES-150-5
3	Controller Card	EBCTR4C.pcb
4	LED Display Card for Type A	S16812B
5	LED Display Card for Type B	S32087A.PCB & S48087A.PCB
6	LED Display Card for Type C	S32087A.PCB & S48087A.PCB
7	Network Interface Card	Moxa NE4110s

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 84 of 94	Signalling (SIG) Maintenance Technical Instruction

8.7 To Change Controller Card for PIDS Display (Industronic Model).



Tools Required:

- Philip Screwdriver
- M3 Screw nut Driver
- M43 Screw nut Driver

PIDS Display Type:


- Type A: Only at KLIA2
- Type B: Only at KLIA
- Type C: KLIA & KLIA2
- Type D: Only at KLIA2

For PIDS Displays (Type A, B, C)

No.	Component	Part Name & Model
1	Power Supply Unit (PSU) for Type A	Meanwell, S-320-5
2	Power Supply Unit (PSU) for Type B & C	Meanwell, NES-150-5
3	Controller Card	EBCTR4C.pcb
4	LED Display Card for Type A	S16812B
5	LED Display Card for Type B	S32087A.PCB & S48087A.PCB
6	LED Display Card for Type C	S32087A.PCB & S48087A.PCB
7	Network Interface Card	Moxa NE4110s

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 85 of 94	Signalling (SIG) Maintenance Technical Instruction

8.8 LED Module Display Card Replacement (Industronic Model).



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 86 of 94	Signalling (SIG) Maintenance Technical Instruction

9 TMS Maintenance Technical Instruction

9.1 Functions of Abbreviation in the Timetable Planning

D- Availability stop

Causes the next set point to not setting automatically. As the train approaches, 'Operate signals' request will be activated.

H- Absolute stop

Same as D, except without an 'Operate Signals' request.

A (K)- Waiting for connection

Next set point is not set until the reference train has reached the programmed place and the connection time programmed in the system has elapsed.

B (K)- Waiting for delay

The next set point is not set until the reference train has reached the programmed place.

T (K)- Departure time

The next set point is not set until the departure time is reached.

S- Setting-back train

Drive train in the opposite direction with the same train number.

W- Push and Pull train

Travels in the opposite direction with a new train number.

N- New train number during stop

The new train number can be changed during a stop,

M- New train number on a moving train

Train number is changed when the train passes the station.

Z- Stop at the block signal

If a train has to stop at a block signal lying along the routes, a Z is programmed. Without a Z, the corresponding track is used as a diversion point for trains passing through.

F- Train number stepping

This function is used to step a train number to any routing track.

X- Interruption in the route


Set at the place where the train left the train guidance zone. The routing track where the train re-enters the train guidance zone is programmed as the next routing track.

V- Delayed start

The driving position for a signal may be delayed in order to put back the start of barrier procedure in case of trains that stop or in order to prevent the premature blocking of the other routes.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 87 of 94	Signalling (SIG) Maintenance Technical Instruction


9.2 Checking and Testing Data Transfer Tools on CST 70 and CST 71.




Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 88 of 94	Signalling (SIG) Maintenance Technical Instruction

9.3 TSP task fail to export to File exchange server.

1. If the tool no longer works, error messages are displayed on the user interface. These messages are not always written to the log file.
2. The lines “Last Transfer time <computer>” show the last transfers. This is useful for tests. If a file is changed on the computer with the monitored directory, e.g. new file name, the display should refresh.




3. You need full access to the directories and this only works with iadmin <password>. Best practice for configuring this:
 1. Login as support and Password as xxxxxxx
 2. Open Total Commander → (Right click to run as administrator)
 3. Map a network drive (Net)




4. Choose any drive letter and key in the path of the remote (both WorkStation)
 - X: [\\10.3.5.70\iltisap](#) → [Maintenance Workstation](#)
 - Y: [\\10.3.24.71\iltisap](#) → [OCS Workstation](#)
5. Click reconnect at logon and connect using different credentials
6. Enter network password; use iadmin <password>, this step must be done by SYS-SIG TMS Administrator staff.

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 89 of 94	Signalling (SIG) Maintenance Technical Instruction




7. Logon File Exchange Server (NMS)

- Login as Iltisexport and enter password SigILTIS2017
- Double click FILE and choose Data Export.
- Choose File Maintenance and check all folder and file.
- Log out.




<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 90 of 94	Signalling (SIG) Maintenance Technical Instruction

9.4 Key in the TMS username and download the log File



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 91 of 94	Signalling (SIG) Maintenance Technical Instruction

9.5 Perform Task TSP using CD/DVD Rom at ILTIS workstation



Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 92 of 94	Signalling (SIG) Maintenance Technical Instruction


9.6 Restoration of YST 28 or YST 29 or both goes down.

WARNING:

WHEN POWER FAILURE OCCURRED AND ANY YST OR BOTH YST SERVER GOES DOWN, PLEASE DO NOT SWITCH OFF OR ON MANUALLY AT YST SERVER.

IMPACT FOR DOING WRONG ACTION WILL COST YST HDD SERVER MAYBE CORRUPTED AND CRUSHED.

Refer below for the action need to be done.



<i>Location</i>	<i>Reference</i>	<i>Rev.</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Title</i>
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 93 of 94	Signalling (SIG) Maintenance Technical Instruction

10 Operating Instruction For UPS (Uninterruptable Power Supply).

10.1 UPS Maintenance START - UP Procedure

WARNING: 'A WRONG PROCEDURE COULD DISCONNECT THE LOAD'

UPS IN MAINTENANCE BY-PASS operation, with service switches Q1 and Q4 OFF, and Q2 ON and battery F8-F9 OFF.

- LCD will display "LOAD OFF".
- LED 2, 8, 9 & Service check, Alarm & Light "ON".
- LED 1, 3, 4a, 4b, 5, 6, 7 & Battery level Indicator "OFF".

STEP – 1

TURN SWITCH "Q4" TO "ON" POSITION.

- LCD will display "LOAD OFF".
- LED 3 Flashing.
- LED 1, 2, 8, 9 & Service check "ON".
- LED 4a, 4b, 5, 6 & 7 "OFF".
- Alarm & Light "ON".
- After 30 to 40 Second LED 3 Steady &
- Green LED beside Battery Fuse Lights up.

STEP – 2

PUSH IN "ON" THE BATTERY FUSE 8 & 9.

- LED 4b & Battery level Indicator "ON".
- Alarm & Light "OFF".

STEP – 3

"Q1" SWITCH "ON" POSITION.

- LCD will display "LOAD ON BY-PASS".
- LED 1, 2, 3, 4b, 7, 8, 9 "ON".
- LED 4a, 5, 6 "OFF" & Service check "OFF".

STEP – 4

"Q2" SWITCH "OFF" POSITION.

- LED 1, 2, 3, 4b, 7 & 8 "ON".
- LED 4a, 5, 6 & 9 "OFF".

STEP – 5

PRESS KEY once

- LED 1, 2, 3, 4b & 8 "ON".
- LED 5 Start Flashing for 5 Seconds then Steady.
- LED 6 will "ON" after 20 Seconds.
- LED 4a, 7 & 9 "OFF".
- LCD will display "LOAD ON INVERTER".

Location	Reference	Rev.	Date	Page No.	Document Title
E-MAS Offices	E00.OME.M12950.BT.1001	A	26.8.2021	Page 94 of 94	Signalling (SIG) Maintenance Technical Instruction

10.2 UPS Maintenance BY – PASS Procedure

WARNING: 'A WRONG PROCEDURE COULD DISCONNECT THE LOAD'

UPS IN NORMAL operation, with service switches Q1 and Q4 ON, and Q2 OFF, battery F8-F9 ON and Load On Inverter.

- LCD will display “LOAD ON INVERTER”.
- LED 1, 2, 3, 4B, 5, 6 & 8 “ON”.
- LED 4a, 7 & 8 “OFF”.

STEP – 1 PRESS 0 KEY once, Then press again (within 5 Seconds)

- LED 5, 4a, 6 & 9 “OFF”.
- LCD will display “LOAD ON BY-PASS”.
- LED 1, 2, 3, 4b, 7 & 8 “ON”.

STEP – 2 “Q2” SWITCH “ON” POSITION.

- LED 1, 2, 3, 4b 7, 8 & 9 “ON”.
- LED 4a, 5 & 6 “OFF”.

STEP – 3 “Q1” SWITCH “OFF” POSITION.

- LED 1, 2, 3, 4b 7, 8, 9 & Service Check “ON”.
- LED 4a,5 & 6 “OFF”.

STEP – 4 PRESS “LOAD OFF” PUSH BUTTON by lifting red cover.

- LCD will display “LOAD OFF”.
- LED 1, 2, 3, 4b, 8, 9 & Service check “ON”.
- LED 4a, 5, 6 & 7 “OFF”.

STEP – 5 TURN SWITCH “Q4” TO “OFF” POSITION.

- LCD will display “LOAD OFF”.
- LED 2, 4a, 8, 9 & Service check “ON”.
- LED 1, 3, 4b, 5, 6 & 7 “OFF”.
- Alarm & Light “ON”.

STEP – 6 BATTERY FUSE 8 & 9 “OUT”.

- LCD will display “LOAD OFF”.
- LED 2, 8, 9 & Service check, Alarm & Light “ON”.
- LED 1, 3, 4a, 4b, 5, 6, 7 & Battery Level Indicator “OFF”.

Press “mute” button to acknowledge Alarm.