

#104129

ERL MAINTENANCE SUPPORT SDN BHD

(Company No. 498574-T)



ROLLING STOCK DEPARTMENT IN-HOUSE TECHNICAL INSTRUCTION

GEARBOX TEST BENCH OPERATING INSTRUCTION

Doc. No. D10.OMR.M83000.PT.1001.B







Certified to ISO 9001:2008
Cert. No. AR 2874

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	2 of 11	Gearbox Test bench – Operating Procedure

Release

Released:	Ham MW	MTN HoD	03 06 09	
Checked:	Mohd Jamil	RST HoD	03 06 09	
Checked:	Mohammad.J	RST QMR	03.06.09	
Author:	Vijendran Veeraya	RST Engineer	14/05/09 03/06/09	
	Name	Dept./Position	Date	Signature

Amendments or additions to this procedure must be indicated with a vertical black line in the adjacent left margin.

Change Record and Configuration Control

B	03/06/09	Relevant changes carried out after gearbox trial runs	VJV
A	14/05/09	New	VJV
Revision	Date	Modification	Name

Rolling Stock Department

<i>Document Type</i>	<i>Reference</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Name</i>
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-.06-09	3 of 11	Gearbox Test bench – Operating Procedure

TABLE OF CONTENTS

	Page
1 Purpose.....	4
2 Scope, Distribution & Access	4
3 Gearbox Test Bench	4
4 Procedure	5
4.1 Gearbox Setting	5
4.1.1 Setting-up Datalogger	7
4.2 Power Supply Set-up	8
4.3 Start-up	8
4.3.1 Auto Mode.....	9
4.3.2 Manual Mode	9
4.4 Stopping the Test.....	10
4.5 Results interpretation	10
Attachments	11
Appendices	11

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	4 of 11	Gearbox Test bench – Operating Procedure

1 Purpose


The purpose of this document is to provide the user of the usage of SZ16 gearbox test bench for the purpose of verifying the results of the gearbox overhaul

2 Scope, Distribution & Access

The scope of this work falls under RST maintenance. The distribution is open to all RST Maintenance staffs. The access to this document will be made available to all RST staffs via department online folder.

3 Gearbox Test Bench

Below are the equipment of the test bench



Picture 1

A - Main Control Panel


B - Human Machine Interface (HMI) Panel



Picture 2


Siemens 22kW motor

Flexible Coupler



Picture 3

Magnetic Head Temperature Sensor x 10



Picture 4

Sump Temperature Sensor. x 1

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	5 of 11	Gearbox Test bench – Operating Procedure



Picture 5

Vibration
Sensor



Picture 6


Data Logger
Hioki 8421-51

4 Procedure


4.1 Gearbox Setting

Attention: Gearbox Stand and Axle Preparation

- 1) *Mount dedicated set of inner rings to the axle.*
- 2) *Place inner ring – 50mm from the edge of axle*
- 3) *Replace the crowned rollers with bronze material rollers*
- 4) *The gap between the axle and fiber holder – 1 mm*
- 5) *The rollers & inner rings needs to be oiled before starting*



- A. Ensure the gearbox with axle is placed correctly on the balancing machine stand. The inner ring sits on the top of the bronze rollers. Work shall be carried out cautiously as to avoid damage to axle.
- B. Bring forward the Siemens 22kW operating motor and couple with the gearbox shaft with flexible coupler.
- C. The flexible coupler shall engaged at least 30mm on both shafts and shall be tightened properly by hand. (refer to picture 7)




Picture 7
Engaging both shafts
with flexible coupler

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	6 of 11	Gearbox Test bench – Operating Procedure

- D. Perform shaft alignment using the shaft alignment tool (SKF TEMA 2). This tool shall only be operated by trained personnel. Refer attachment 2 for the list of trained personnel.
- E. The deviation shall not be more than the below value. It will be shown in the screen
 - 1) 0.05 – angle between center line (top of display)
 - 2) 0.03 - parallel off-set of the two center line (2nd top of display)
- F. Attach the magnetic thermocouples to the location in accordance with the attached drawing. (attachment 1)
- G. Replace the oil sump nut (picture 8) with the oil sump thermocouple. Ensure the sump is filled with gearbox oil.



Picture 8

Red-circled area is the location of oil sump nut

H. The table below shows the descriptions and connections for the measuring equipments

No	Equipment	Description	Location	Cable Type.	Cable No. & Connection Ch. at data logger	Measurement Range
1	HMI panel input on speed. (RPM)	RPM measurement	Cable connection from HMI panel	Blue wire cable	P01 to Ch.1	1 volt = 750 rpm (Max = 6000rpm)
2	HMI panel input on current. (Amps)	Current reading	Cable connection from HMI panel	Blue wire cable	P02 to Ch.2	1 volt = 13 amps
3	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 3 as in drawing in attachment 1	Thermo couple wire	P03 to Ch.3	Type K Temp. range. (-200C – 1100C.)
4	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 4 as in drawing in attachment 1	Thermo couple wire	P04 to Ch.4	Type K Temp. range. (-200C – 1100C.)
5	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 5 as in drawing in attachment 1	Thermo couple wire	P05 to Ch.5	Type K Temp. range. (-200C – 1100C.)

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	7 of 11	Gearbox Test bench – Operating Procedure

6	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 6 as in drawing in attachment 1	Thermo couple wire	P06 to Ch.6	Type K Temp. range. (-200C – 1100C.)
7	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 7 as in drawing in attachment 1	Thermo couple wire	P07 to Ch.7	Type K Temp. range. (-200C – 1100C.)
8	Magnetic Thermocoupler	Measuring bearing temperature	Pos. 8 as in drawing in attachment 1	Thermo couple wire	P08 to Ch.8	Type K Temp. range. (-200C – 1100C.)
9	Sump temperature sensor	Measuring sump oil	Pos. 9 as in drawing in attachment 1	Thermo couple wire	P09 to Ch.9	Type K Temp. range. (-200C – 1100C.)
10	Magnetic Thermocoupler	Measuring ambient temperature	Place at the side of access door	Thermo couple wire	P10 to Ch.10	Type K Temp. range. (-200C – 1100C.)
11	Vibration sensor Power Supply From vibration device tapped from HMI power supply	Measuring the general vibration of the gearbox	Pos. 11 as in drawing in attachment 1. <u>Controller to gearbox</u> Connection at -DC (17), SIG (20), and Com (21) white wire (vibration sensor wire)	Vibration sensor White wire from Vibration controller to sensor Blue wire from controller to data logger	<u>Controller to data logger</u> Connection at -10v and +10v Blue wire to Ch.11	2mms/V

* Thermocouple cable polarity – Red is positive and black is negative

4.1.1 Setting-up Datalogger

- A. Connect the power supply and switch on the datalogger via the toggle switch located at the side of the datalogger
- B. Wait and let the datalogger boot and stabilise
- C. Press setup (purple key on the top left)
- D. Press down arrow key (black with no words printed on) to highlight system at the bottom of the screen
- E. Press the grey arrow key on the left of the black arrow keys, this will bring to the next screen

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-.06-09	8 of 11	Gearbox Test bench – Operating Procedure

- F. Change to the Setting tab, using the blue fast forward keys
- G. Using the black arrow keys, go to No.1 SZ16 Gearbox and highlight "Load", then press the grey arrow key, follow by the green "start" key.
- H. Exit the system screen by pressing the purple setup button
- I. Ensure the print paper is aligned properly to its outlet slot, if needed, press the black "Feed" button
- J. The datalogger is now ready for use

4.2 Power Supply Set-up

- A. Plug the operating motor plug in the 3-phase power socket located at the beam. (refer picture 9)



Picture 9

Operating Motor 3 phase
connector and socket

- B. Switch the main-power ON inside the main control panel.
- C. Check to see if the main inverter and vibration sensor controller power up Switch "ON"

4.3 Start-up

Attention: Safety Instruction Before Start-up

- 1) Before any start-up in auto or manual mode, manually run the machine at 300rpm. The machine shall be inspected for any abnormalities.
- 2) If any abnormally found, including unusual sound or movement of the any part of the test bench and axle being tested. The test shall be discontinued until investigation and rectified are carried.
- 3) During the initial spin, apply a coat of oil on the surface of the inner ring.
- 4) Close the door before proceeding with the auto test.
- 5) No one is allowed within the cubicle of the test bench when test is under progress.
- 6) Maximum speed setting shall not exceed 6000 rpm

- A. Select "Fix Mode" on the HMI panel
- B. Select Auto or Manual for Auto Mode or Manual Mode
(select "Main Page" to return to previous screen)
- C. Press "start" on the datalogger first

Rolling Stock Department

Document Type	Reference	Date	Page No.	Document Name
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-.06-09	9 of 11	Gearbox Test bench – Operating Procedure

4.3.1 Auto Mode

- A. Select Auto Page, and press Start button.
- B. Ensure the datalogger start to show the graph
- C. The motor will now run at the following speed automatically
 - 1) 0 – 2000rpm movement counter clockwise (CCW) hold for 250 seconds
 - 2) 2000 – 4000rpm movement CCW hold for 300 seconds
 - 3) 4000 CCW – 2000rpm clockwise (CW) hold for 300 seconds
 - 4) 2000 – 4000rpm CW hold for 300 seconds
 - 5) 4000 – 6000rpm CW hold for 700 seconds
 - 6) 6000 CW – 6000rpm CCW hold for 700 seconds

Ramp-up rate at 40rpm/s
Ramp-down rate at 80rpm/s
Total Running time is approximately 54minutes

- D. At the end of the cycle (6), the motor will start braking and come to a stop.
- E. The datalogger will automatically stop at the 55th minute.
- F. Upon seeing the below message at the data logger
 - 1) Storage finish
 - 2) Saving data
 - 3) Making WaveformThe storage is complete.
- G. Tear off the print out from the datalogger to include it as part of the overhaul documentation. Record down the remaining paper length on the print paper of the machine. A minimum length of 400mm is required. Otherwise, replace paper role
- H. Press the black "Card" key
- I. Look for the last file saved – the files are saved with the date and timestamp. Write down the filename with prefix of SZxx.mem on the print out. When done, press "setup" to exit.
- J. Switch off all units

4.3.2 Manual Mode

Manual mode is used for low spin cycle only (below 1000rpm). If there are any deviations of use, user shall obtain prior approval from RST HoD

- A. Select Manual page
- B. Manual Page screen appears
(Select "Main" to return to previous screen)
- C. Manually insert the desired speed and time frame.
- D. Press the start button

Rolling Stock Department

<i>Document Type</i>	<i>Reference</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Name</i>
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	10 of 11	Gearbox Test bench – Operating Procedure

4.4 Stopping the Test

The test shall be stopped if

- A. There are any abnormally or loud/unusual sounds
- B. Heavy vibration on the stand or axle, reading exceeds 12.5 mm/s
- C. Temperature reading at the data loggers exceeds 90 degree Celsius

Press the stop button on the HMI panel to stop the sequence

Use the emergency stop push button for emergency purpose only, the buttons are located at:

- A. 1 unit is located on the HMI panel
- B. 1 unit is located at the fence, nearby the motor
- C. 1 unit is located at the fence, nearby the oil sump

The emergency stop switch immediately cut-off the running sequences and stops the motor.

4.5 Results interpretation

This test at the test bench is a comparison test. It is the intention to collect at least 5-6 units of gearbox data before a realistic benchmark can be established. Overall, the rate of temperature increase will be the tale telling sign if a particular gearbox has been overhauled correctly. Therefore, a quicker than usual rising temperature may indicate a potential problem.

Rolling Stock Department

<i>Document Type</i>	<i>Reference</i>	<i>Date</i>	<i>Page No.</i>	<i>Document Name</i>
RST In-house Technical Instruction	D10.OMR.M83000.PT.1001.B	03-06-09	11 of 11	Gearbox Test bench – Operating Procedure


Attachments

- Attachment 1: Drawing of Gearbox with sensor positioning
- Attachment 2: List of Personnel Trained on TEMA Alignment Tool
- Attachment 3: Data Logger Channel Set-up parameters

Appendices

1. Gearbox Vibration Test Bench (Contractors Manual) – D00.DWE.M83550.NZ.1001.A
2. Siemens MicroMaster 440, Operating Instruction and Parameter List –
D00.DWE.M83550.NA.1001.A and D00.DWE.M83550.NA.1002.A

Pos. 10/1 6




Pos. 3 - 8 Lager temp./ bearing temp., Pos. 9 Sumpfltemp./ Sump temp.,
Pos. 10 Raumtemp./ ambient temp., Pos. 11 Schwingungsaufn./ Vibration

ERL Maintenance Support Sdn Bhd


(Company No. 498574-T)

Attachment 2: List of RST Personnel Trained on TEMA Alignment Tool


No	ID No	Name	Trained date
1	200166	Mohd Azhar	Trained during product delivery.
2	200234	Mohd Nurul	Trained during product delivery.
3	200250	Khairunizam	24/04/09
4	200224	Mohd Shamsul	24/04/09
5	200282	A. Hisham Rusdi	24/04/09
6	200247	Saifullah Paujan	24/04/09
7	200167	Abd. Muiz	24/04/09
8	200217	Addi b. Yassin	24/04/09



Channel 1



Channel 2




Channel 3




Channel 4




Channel 5




Channel 6




Channel 7




Channel 8




Channel 9




Channel 10



Channel 11




Set Up Page



Keypad



Upper Part of Keypad



Lower Part of Keypad